



## VISCO-C 501

### Waterproofing additive that can be used in mortar and concrete

#### DESCRIPTION:

Waterproofing additive that can be used in mortar and concrete.

#### ADVANTAGES:

Water repellent.

It prevents the capillary from absorbing water.

Used in machine plasters.

Ready to use.

#### USAGE AREAS:

Waterproof, mortar, concrete, screed manufacturing,

Forming waterproof plaster mortar.

In the formation of waterproof brick mortar.

To increase the water impermeability of precast exterior elements.

Can be used in all cement, lime-based mortars.

Can be used in tunnels, foundations, culverts, canals, swimming pools.

#### TECHNICAL SPESIFICATION :

( 23 °C Temperature and 50 % for relative humidity)

Colour : Brown

Density 20°C : 1,1 gr/cm<sup>3</sup>

\*\*\*These values were obtained as a result of laboratory tests, just contain finished applications according to drying time performance. Due to differences in temperature and humidity values in the construction site, the values may change.

#### APPLICATION METHOD:

##### Preparation Of The Mixture:

Enough clean water is poured into an empty and clean bucket and dosed between 0,5 % and 0,8% according to the quality of the mortar to be mixed into the mortar water. The mortar is made with the formed water. The product must be put into the mixing water and not directly added to the mortar.

#### ISSUES TO BE CONSIDERED:

Temperature should be between +5 °C and +35 °C during the application.

Do not apply on surfaces that are at risk of frost.

In addition, it should not be applied in extremely hot, rainy or windy weather.

These time can change according to temperature and moist ratio.



## VISCO-C 501

### Waterproofing additive that can be used in mortar and concrete

#### CLEANING OF INSTRUMENTS:

DAYMAN VISCO –501 should be cleaned by water just after the application.

#### CONSUME:

%0,5 and % 0,8 of the total cement percentage.

#### PACKING:

30, 00 kg. Plastic Bin

80x120 Pallet Dimension

24 Qty.on Pallet

5, 00 kg. Plastic Bin

80x120 Pallet Dimension

120 Qty.on Pallet

#### COLOR:

Brown

#### SHELF LIFE:

1 year from the production date under proper storage conditions.

Opened packages should be kept tightly closed.

Wear work clothes, protective gloves, glasses and masks should be used during application.

#### SAFETY RECOMMENDATIONS:

Skin and eyes should not be contacted, in case of contact with wash plenty of water and soap, if swallowed seek medical attention immediately.

Food and beverage materials should not be kept in the application area and should not be eaten.

Store out of reach of children.

This product packaging must be disposed of in accordance with applicable laws.

This responsibility is belonging the end user.

For more information please check the Material Safety Data Sheet.

#### LIMITATIONS OF LIABILITY:

The information in this technical data sheet is given according to technical information, experience and test result.

As GENERALTÜRK A.Ş. cannot control the usage of the product that used under which kind of conditions, it does not accept any responsibility for the application result and does not guarantee it.

The product suitability for the product user should be tested and decided accordingly.



## VISCO-C 501

### Waterproofing additive that can be used in mortar and concrete

All products should be considered in the advice of those technical knowledge and equipment.

GENERAL TURK A.Ş can not accept any responsibility that occurs because of misuse, it only responsible for the written suggestions that shows the products where and how use.

GENERALTÜRK A.Ş. It may change the properties of its products without announcement.

The technical data sheet is valid until the next time it is printed and all previous technical data sheets invalidate the description / January 2020

<b>CE</b> <b>2765</b>	
<b>GENERALTURK TEKNİK YALITIM</b> <b>KİMYA END. SAN. TİC. A.Ş.</b> YUNUSELİ MH. 15. YAVUZ SK. NO: 21 OSMANGAZI - BURSA / TÜRKİYE <b>20</b>	
<b>2765 - CPR - 0156</b> <b>EN 934 - 2</b>	
<b>VISCO - C 501</b>	
<b>CONCRETE ADMIXTURES</b>	
<b>Intended use in concrete for water resisting;</b>	
Colour	Brown
Density 20°C	1,1 gr/cm <sup>3</sup>